



# C-FORM fire protection cut-out including HENSOMASTIK<sup>®</sup> Mixed penetration seal EI90 / EI120

The C-FORM fire protection cut-out is a prefabricated formwork made of concrete using 3D printing to ensure fire protection in buildings.

- Moisture-resistant level
- No need to formwork component openings on the construction site
- No fall protection required for two-panel bulkheads
- Fire protection already specified when concreting the raw ceiling
- Can also be used as a penetration seal in walls
- Assignment according to ETA 20/1309 and assembly instruction
- Can also be used with other Hensel penetration sealing systems

## PRODUCT INFORMATION

#### C-FORM advantages during installation

- Reduction in working time (cutting and assembly time)
- Reduction of material (wood, formwork panels, etc.)
- Fall protection no longer necessary
- Precisely fitting delivery of the elements (no measuring required for the recess)
- Fire protection is 70 % completed; costs are reduced
- Fewer problems during acceptance for fire protection, as bulkheads are already installed and pipe clearances are maintained during installation

#### C-FORM advantages while routing

- Sufficient space: Until now, there has often not been enough space for the subsequent, precisely fitting, insertion of the mineral wool panels, which made the insertion of a soft penetration seal often very complicated and time-consuming
- Penetration seals already installed: Plumbers, electricians etc. have to adapt their lead-throughs to the soft penetration seal
- Liability: Distances, media etc. are adhered to, therefore no liability issue

Note: This product information is for your consultation.

It do not serve in lieu of the details in the underlying European Technical Assessment ETA 20/1309.





C-FORM fire protection cut-out



HENSOTHERM<sup>®</sup> pipe collar



HENSOTHERM<sup>®</sup> 7 KS Gewebe (fabric)



### RUDOLF HENSEL GMBH Lack- und Farbenfabrik

Lauenburger Landstraße 11 21039 Börnsen | Germany

Tel. +49 40 72 10 62-10 Fax +49 40 72 10 62-52

Email: contact-rh@rudolf-hensel.de Internet: www.rudolf-hensel.de

Orders: -40 Technical advice / sales D/A/CH: -44, international: -48

Extensions:





Rudolf Hensel GmbH 02/24