

Declaration of Performance

According to Annex III of the Regulation (EU) No. 305/2011

HENSOTHERM® 7 KS

HENSOTHERM® 7 KS viskos

HENSOTHERM® 7 KS Gewebe

LE_7KSG_GB_V03_00

- | | |
|--|---|
| 1. Product Type
Unique identification code of the product type | HENSOTHERM® 7 KS
HENSOTHERM® 7 KS viskos
HENSOTHERM® 7 KS Gewebe |
| 2. Type
Batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4) | See label on the bucket |
| 3. Indented Use
or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer | Fire-protection products for fire sealing and fire stopping purposes. Intended to be used as an essential component in construction products, construction elements, assemblies, kits and special constructions which need to meet requirements concerning the safety in case of fire. In case of fire, the products delay the heat transfer and the spread of fire by expanding under the impact of high temperatures. |
| 4. Name, registered Trade Name
or registered trade mark and contact address of the manufacturer as required under Article 11 (5) | Rudolf Hensel GmbH
Lack- und Farbenfabrik
Lauenburger Landstraße 11
21039 Börnsen
Germany |
| 5. Contact Address
Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) | Not relevant (see 4) |
| 6. AVCP
System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V | System 1 |
| 7. Notified Body (hEN)
In case of the Declaration of Performance (DoP) concerning a production product covered by a harmonised standard | Not relevant |

8. Notified Body (ETA)

In case of the Declaration of Performance concerning a construction product for which a European Technical Assessment (ETA) has been issued

European Technical Assessment ETA 16/0369 issued by Deutsches Institut für Bautechnik (DIBt). EAD 350005-00-1104 was used as European Assessment Document (EAD). The notified body 0761 performed third party tasks as set out in Annex V under System 1 and issued Certificate of Conformity 0761-CPR-0293.

9. Declared Performance

Essential Characteristics	Performance	Technical Specification
Mechanical resistance and stability	Not relevant	
Resistance to fire	Not relevant	
Reaction to fire		DIN EN 13501-1
- HENSOTHERM® 7 KS Gewebe of a nominal thickness of 1 mm, free standing or on mineral substrates of a minimum density of 525 kg/m ³ and on metal substrates with a melting point at least of 500°C or on substrates classified class A1 or class A2-s1	Class C-s2, d0	
- HENSOTHERM® 7 KS Gewebe of other nominal thicknesses or on other substrates HENSOTHERM® 7 KS HENSOTHERM® 7 KS viskos	Class E	
Release of dangerous substances	The product specification has been compared with Annex XVII of REACH and the ECHA Candidate List of Substances of Very High Concern and it does not contain such substances.	
Safety in use	Not relevant	
Protection against noise	Not relevant	
Energy, economy and heat retention	Not relevant	
Top coat compatibility	Based on acrylate dispersion, alkyd resin, polyurethane acrylate, and epoxy resin	EOTA TR 024
Additional verification of resistance	- Exposure to a constant temperature of 80 °C for 40 days - Exposure to solvents (tested with butyl acetate, butanol, white spirit, and fuel oil) - Short term exposure to constant wetness over 4 weeks Contact with plastics (PVC, PE)	EOTA TR 024
Durability	Type X, Y ₁ , Y ₂ , Z ₁ , and Z ₂	EOTA TR 024

10. The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This Declaration of Performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Note:

Besides the Declaration of Performance assessments, technical data sheets and material safety data sheets for our HENSOTHERM® and HENSOMASTIK® products are available as pdf download on www.rudolf-hensel.de. For further questions concerning our products, our technical team is available by phone +49 40 721062-48.

Signed for the manufacturer and on behalf of the manufacturer:

Börnsen, 2019-05-13



Volker Thewes
Managing Director



Anja Peter (Dipl.-Ing. FH)
Technical Director

The information provided herein reflects the current state of our technical testing and experience with the use of this product. However, the buyer/user is hereby not relieved of their duty, at their own responsibility, to properly examine our materials for their suitability for the intended use based on the respective site conditions. Legal claims for damages arising from the use of this product for purposes other than, or in a manner that differs from, the description contained herein without our prior written approval are precluded and may not be asserted against us. In light of the circumstance that we have no influence over site conditions and various factors that could influence the performance and use of our product, a guarantee of results or liability, regardless of legal grounds, cannot be derived from this information or from verbal consultation provided by one of our employees unless we may be accused of intent or gross negligence. Our General Terms and Conditions apply for all other purposes. The most recent version of our technical data sheet is valid and may be requested from the Rudolf Hensel GmbH or downloaded at www.rudolf-hensel.de

© Rudolf Hensel GmbH

Page 3 of 3

RUDOLF HENSEL GMBH

Lack- und Farbenfabrik

Lauenburger Landstraße 11
21039 Börnsen | Germany

Tel. +49 (0) 40/72 10 62-10
Fax +49 (0) 40/72 10 62-52

E-Mail: info@rudolf-hensel.de
Internet: www.rudolf-hensel.de

