


Profile / Profilabmessungen

IPN	Wandstärke	T	5,9	6,8	7,7	8,6	9,5	10,4	11,3	12,2	13,1	14,1	15,2	16,2	17,3	18,3	19,5	20,5	21,6	23,0	24,3	25,6	27,0	30,0	32,4	
	Flanschbreite	B	42	50	58	66	74	82	90	98	106	113	119	125	131	137	143	149	155	163	170	178	185	200	215	232
	Steghöhe	H	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	425	450	475	500	550	600	650
Profilbezeichnung IPN			80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	425	450	475	500	550	600	650
U/A (4-seitig)			402	349	309	276	252	229	212	196	183	170	158	149	140	133	125	119	113	107	101	95	91	85	76	

IPE	Wandstärke	T	5,2	5,7	6,3	6,9	7,4	8,0	8,5	9,2	9,8	10,2	10,7	11,5	12,7	13,5	14,6	16,0	17,2	19,0
	Flanschbreite	B	46	55	64	73	82	91	100	110	120	135	150	160	170	180	190	200	210	220
	Steghöhe	H	80	100	120	140	160	180	200	220	240	270	300	330	360	400	450	500	550	600
Profilbezeichnung IPE			80	100	120	140	160	180	200	220	240	270	300	330	360	400	450	500	550	600
U/A (4-seitig)			429	388	360	336	310	292	269	254	236	227	215	200	186	174	162	150	140	129



HE-A	Wandstärke	T	8,0	8,0	8,5	9,0	9,5	10,0	11,0	12,0	12,5	13,0	14,0	15,5	16,5	17,5	19,0	21,0	23,0	24,0	25,0	26,0	27,0	28,0	30,0	31,0
	Flanschbreite	B	100	120	140	160	180	200	220	240	260	280	300	310	330	350	390	440	490	540	590	640	690	790	890	990
	Steghöhe	H	96	114	133	152	171	190	210	230	250	270	290	310	330	350	390	440	490	540	590	640	690	790	890	990
Profilbezeichnung HE-A (IPBI)			100	120	140	160	180	200	220	240	260	280	300	310	330	350	390	440	490	540	590	640	690	790	890	990
U/A (4-seitig)			265	264	253	234	225	212	196	178	164	154	142	135	128	120	113	107	104	102	100	96	94	91	89	

HE-B	Wandstärke	T	10,0	11,0	12,0	13,0	14,0	15,0	16,0	17,5	18,0	19,0	20,5	21,5	22,5	24,0	26,0	28,0	29,0	30,0	31,0	32,0	33,0	35,0	36,0	
	Flanschbreite	B	100	120	140	160	180	200	220	240	260	280	300	300	300	300	300	300	300	300	300	300	300	300	300	300
	Steghöhe	H	100	120	140	160	180	200	220	240	260	280	300	320	340	360	400	450	500	550	600	650	700	800	900	
Profilbezeichnung HE-B (IPB)			100	120	140	160	180	200	220	240	260	280	300	320	340	360	400	450	500	550	600	650	700	800	900	
U/A (4-seitig)			218	202	187	169	159	147	140	130	127	124	116	110	106	102	97	93	89	87	86	85	82	81	78	

HE-M	Wandstärke	T	20,0	21,0	22,0	23,0	24,0	25,0	26,0	32,5	33,0	39,0	29,0	40,0	40,0	40,0	40,0	40,0	40,0	40,0	40,0	40,0	40,0	40,0	40,0	40,0
	Flanschbreite	B	106	126	146	166	186	206	226	248	268	288	310	320	320	320	320	320	320	320	320	320	320	320	320	320
	Steghöhe	H	120	140	160	180	200	220	240	270	290	310	340	359	377	395	432	478	524	572	620	668	716	814	910	
Profilbezeichnung HE-M (IPBv)			100	120	140	160	180	200	220	240	260	280	300	320/305	320	340	360	380	400	420	440	460	480	500	520	
U/A (4-seitig)			116	111	106	100	96	92	89	73	71	70	60	79	60	60	61	61	63	63	64	65	66	67	68	

© Rudolf Hensel GmbH 09/24

RUDOLF HENSEL GMBH

Lack- und Farbenfabrik

Lauenburger Landstraße 11
21039 Börnsen | Germany

Tel. +49 40 72 10 62-10
Fax +49 40 72 10 62-52

E-Mail: kontakt@rudolf-hensel.de
Internet: www.rudolf-hensel.de

